



NOTES:

1. HOUSING MATERIAL: LCP UL94V-0.
 2. CONTACT MATERIAL: COPPER ALLOY, 0.35 MM THICKNESS.
 3. PLATING: 1, 3, 5, 15, 30u" GOLD PLATED ON CONTACT AREA, 100u" MIN. MATTE TIN PLATED ON SOLDERING AREA, 50u" MIN. NICKEL PLATED OVERALL.
- ELECTRICAL:**
1. VOLTAGE RATING: 125V AC RMS.
 2. CURRENT RATING: 1.5AMP.
 3. CONTACT RESISTANCE: 30MILLIOHMS MAX.
 4. INSULATION RESISTANCE: 500MEGOHMS MIN @500V DC.
 5. DIELECTRIC WITHSTANDING RESISTANCE: 1000V AC RMS 50Hz, 1MIN.

北京玖思启明电子科技有限公司

REV	JIONS-RJ45-0003	DESCRIPTION	DATE
A	1		2013/07/05

X: ±0.30	APPD: Mr.Wu	TITLE:
X: ±0.20	CHKD: Mr.Wu	超薄4.5H RJ45
XX ±0.10	DR: Gao chong	PART NO: JIONS-RJ45-0003
.XXX±0.05	UNITS: mm	DWG NO: www.jions.com.cn
X: ±2°	SCALE: 1:1	客户图
X: ±1°		SHEET: 10/1