



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 30 MILLIOMHSMAX
- 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500 NDC.
- 5. DIELECTRIC STRENGTH : 1000 VAC RMS 50Hz or 60Hz, 1MIN.

MECHANICAL:

- 1. HOUSING & INSERT MATERIAL : PBT UL94V-0.
 - 2. CONTACT MATERIAL : DIAMETER0.45MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
 - 3. SHIELD : 0.20"0.25MM THICKNESS BRASS WITH NI PLATED.
 - 4. MATTING/UNMATTING FORCE : 2.2KG.F MAX.
 - 5. RETENTION STRENGTH : 7.7KG.F MIN BETWEEN JACK AND PLUG.
 - 6. OPERATING LIFE : 600 CYCLES MIN.
- ENVIRONMENTAL:
- 1. STORAGE : -10℃ ~+40℃ RELATIVE HUMIDITY<70%
 - 2. OPERATION : -40℃ ~+85℃

北京玖思启明电子科技有限公司

REV	ECN NO	DESCRIPTION	DATE
A	JIONS-RJ45-0004		2012/03/06

X. ±0.30	APPD: Mr.wu	TITLE:
X. ±0.20	CHKD: Mr.wu	单口带灯RJ45
.XXX±0.10		
.XXX±0.05		

DR: Gus chong	PART NO: JIONS-RJ45-0004	DWG NO:
UNITS: mm	SCALE: 1:1	客户图
		www.jions.com.cn
		SHEET:10/1