



RECOMMENDED PCB LAYOUT(T=1.60±0.15)
COMPONENT SIDE

SPECIFICATION:
INSULATION RESISTANCE: 100MΩ MIN.
DIELECTRIC STRENGTH: 500VDC FOR ONE MINUTE.
CONTACT RESISTANCE: 30mΩ MAX.
OPERATION TEMPERATURE: -20°C~+85°C.

| | | | |
|------|----------|------------------------------------|---|
| 4 | SHELL | SPCC(T=0.20) | OVER-PLATING: Ni 40μ" |
| 3 | TERMINAL | COPPER ALLOY(T=0.20) | CONTACT AREA: G/F UNDER-PLATING: Ni 50μ" |
| 2 | COVER | HIGH TEMPERATURE THERMOPLASTICS | 30%G.F., JL94V-0, COLOR: BLACK |
| 1 | HOUSING | HIGH TEMPERATURE THERMOPLASTICS | 30%G.F., JL94V-0, COLOR: BLACK |
| ITEM | DESC. | MATERIAL | REMARKS |

| | | | | |
|-----------|-------|-----------|----------|----------------------|
| X. ±0.30 | APPD: | Mr.wu | TITLE: | DIP式HDMI A Type, 带锁螺 |
| .X ±0.20 | CHKD: | Mr.wu | | 丝 Female. |
| .XX ±0.10 | | | | |
| .XXX±0.05 | | | | |
| X° ±2° | DR: | Gus chang | PART NO: | JIONS-HDMI-0010 |
| X° ±1° | | | | |

| | | | | | | |
|--------|----|--------|-----|------------------|-----|---------------|
| UNITS: | mm | SCALE: | 1:1 | DWG NO: | 客户图 | SHEET: 1 OF 1 |
| | | | | WWW.JIONS.COM.CN | | REV: |

北京玖思启明电子科技有限公司

| | | | | |
|-----|-----------------|-------------|------|------------|
| A | JIONS-HDMI-0010 | DESCRIPTION | DATE | 2012/02/01 |
| REV | ECN NO | | | |