



MATERIALS
 1. HOUSING : PET.
 2. COVER: PBT
 3. TERMINAL : COPPER ALLOY,
 PLATING : Sn-Plated
 4. PIN : COPPER ALLOY,
 PLATING : Ni-Plated

SPECIFICATION
 1. CURRENT RATING : 20V 4A
 2. DIELECTRIC WITHSTANDING VOLTAGE :
 500V AC R.M.S. FOR 1 MINUTE
 3. INSULATION RESISTANCE : 100MΩ MIN.AT 500V DC.
 4. CONTACT RESISTANCE : 30mΩ MAX.
 5. OPERATING TEMPERATURE : -40°C TO +85°C.

MECHANICAL CHARACTERISTICS:
 1.INSERTION FORCE : 0.3~3.0 KGF
 2.WITHDRAWAL FORCE : 0.3~3.0 KGF
 3.LIFE TEST: 2,000 CYCLES.

A
B
C
D
E
F

1 2 3 4 5 6 7 8 9 10

REV	A	JIONS-DC Jack-0001	2013/08/29
ECN NO		DESCRIPTION	DATE
1			

Jions 北京玖盟启明电子科技有限公司

X. ±0.30	APPD:	Mr.wu	TITLE:
.X ±0.20	CHKD:	Mr.wu	2. ODC Jack 车PIN 大电流
.XX ±0.10	DR:	Gus chong	PART NO: JIONS-0040
.XXX ±0.05	UNITS:	mm	DWG NO: WWJ. JIONS.COM. CN
X' ±2'	SCALE:	1:1	客户图 SHEET:10/1
X' ±1'			REV: