



REV	RECORO	EC.NO	DATE	DR.BR
0	NEW FILE	N/A	2016.04.28	C.Q.ZHANG

注解:

1. 电气性能: 100% 短路、断路、绝缘 测试  
 测试电压: 300V DC  
 导通电阻: 5Ω(最大)  
 绝缘电阻: 2MΩ(最小)
2. 产品符合"ROHS" 环保标准.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE DECIMALS ANGULAR .XX ±0.1 .XXX ±0.05 ±5. DO NOT SCALE DRAWING		北京玖思启明电子科技有限公司	
DRAW	JIONS-0114	CUSTOMER	CUSTOMER
CHECK		PARTS NO.	N/A
APPR		UNITS	SCALE: N/A
		DWG ID	DWG NO.
		V 16 04 034	REV: SHEET
			0 1 OF 1

3	PVC	45P 橙色	4g	
2	插头	8P8C 水晶头 晶片漂金 L:21.5mm	2Pcs	
1	线材	CAT.5e UTP 24AWG(7/0.16BC)*4P(HD-PE 白/橙&白/绿&绿, 白/蓝&蓝,白/棕&棕 ID:0.95)+黑色PVC外被 OD=5.0±0.2 L=3010mm //外被印字:CAT.5e UTP 24AWGX4PR MADE IN CHINA RoHS	1Pc	
序号	项目	数量	项目	